

## Technical Data Sheet

# VFSH116

## Amber

## Herringbone

### Product Details:

|               |                            |
|---------------|----------------------------|
| Product Code  | VFSH116                    |
| Collection    | Natural                    |
| Construction  | Engineered T&G             |
| Species       | Oak                        |
| Product Type  | Engineered Herringbone     |
| Surface       | Brushed                    |
| Finish        | UV Cured Lacquer           |
| Dimensions    | 90 x 10 x 600 mm           |
| Top Layer     | 3 mm – Solid European Oak  |
| Core Layer    | 7 mm – Multi               |
| Grade         | CDE Rustic                 |
| Pack Size     | 3.024m <sup>2</sup>        |
| Pack Contents | TBC                        |
| Joint Type    | Universal Tongue & Grooved |
| Edge Profile  | Bevel Edged on 4 sides     |

### Technical Information:

|                                          |                                                |
|------------------------------------------|------------------------------------------------|
| Origin                                   | Europe                                         |
| UKTR / UK Timber Regulation              | Full documented evidence of legality of timber |
| Janka Hardness                           | Oak 1360 lbf (6000N)                           |
| Slip Resistance                          | EN 14231 (Test Result 70/42 PTV)               |
| European Reaction to Fire Classification | EN 13501-1 (test result Dfl-s1)                |
| Release of Formaldehyde                  | EN 717-1 (Test result E1)                      |
| Thermal Conductivity                     | EN 12524 (Test result: 0.16W/mK)               |
| Tog Rating                               | 1.13                                           |

### Installation Methods:

|                         |                                       |
|-------------------------|---------------------------------------|
| Fully Bonded            | Yes*                                  |
| Secret Nailed           | No                                    |
| Floated on Underlay     | No                                    |
| Over Underfloor Heating | Yes* (fully bonded installation only) |

\*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation.

All Vittoria Flooring floors must be installed by an experienced and fully competent flooring installer who have the necessary skills to complete each installation in line with the BS8201:2011 standard. The responsibility of inspection of goods lies with the installer, and it is their duty to notify Vittoria Flooring of any potential concerns prior to installation. Installation of your Vittoria Flooring floor is considered acceptance of goods.

### Grading: Rustic

This product is a rustic grade floor, meaning it will contain varying amounts of live and dead filled knots. In addition, the floor will contain Heartwood and Sapwood, offering a wider range of colour variation, End Split & Checks can be expected (cracks along the growth ring). The colour of the filler used on this floor is intended to complement the natural structure of the wood, and such may contrast the surrounding timber, as can be seen in knots. This may vary from batch to batch.

### Maintenance

Sweep with a soft bristle brush, or the parquet attachment on your vacuum cleaner. Always ensure you are using PH Neutral cleaners and avoid soaking the floor with water. Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture.

### Post-Installation

**DO NOT COVER THIS PRODUCT WITH A NON-BREATHABLE COVERING FOR LONGER THAN 1 WEEK.**

Prolonged covering may create a micro-climate which can damage the protective top layer. Underfloor heating will greatly magnify the affect.

## Vittoria Flooring

Email [hello@vittoriaflooring.co.uk](mailto:hello@vittoriaflooring.co.uk)  
Visit [www.vittoriaflooring.co.uk](http://www.vittoriaflooring.co.uk)

© This technical data sheet was written by Vittoria Flooring a trading name of V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. It is the duty of the customer to confirm the specification of their chosen floor upon purchasing. Wood flooring is a natural product with variation in colour.